



Universidad de Oviedo Universidad de Vigo



TECHNOLOGY OFFER

DRONE TECHNOLOGY AND METHOD FOR THE REMOTE MEASUREMENT, CHARACTERIZATION, INSPECTION AND DIAGNOSIS OF ANTENNAS

INNOVATIVE ASPECTS

- ✓ It can be controlled by just one operator with low supervision and expertise, and it allows the measurement to be done in less time than a manual system.
- ✓ The system and methods implemented allow identifying deformations in the structure of the antenna or malfunctioning antenna radiating elements, apart from providing the antenna radiation pattern and the size of the safe perimeter volume around the antenna or radiating system.
- ✓ No need to interrupt the service of the communication system: measurements are acquired in real operational conditions.
- ✓ The system and methods allows retrieving phase information from amplitude-only measurements, and advantage over existing airborne-based measurement systems.
- ✓ The system provides spatial resolution ≤ 3 cm, between two adjacent positions, and the aerial module is capable of positioning with an accuracy ≤ 3 cm.
- ✓ It allows working with arbitrary geometry trajectories not necessarily adjusted to a canonical measurement surface or volume.
- ✓ It can be implemented with one or more aerial modules.

ABSTRACT

In the field of radio-communications, the measurement and characterization of antennas and/or other radiating systems is one of the fundamental aspects for the verification of the correct operation of a communications system. The capability of measuring the antenna in real operational conditions is of special interest, since it allows the evaluation of the distortions that can produce such real conditions in the initial design specifications

This invention relates to an airborne system for the remote measurement, characterization, inspection and diagnosis of antennas or other radiating systems, comprising at least one aerial module, a ground station and a communication system between those elements. The invention also relates to a method of processing the radiated electromagnetic field for obtaining the distribution of the antenna aperture field from which it is possible to perform the diagnosis of such antenna, as well as to determine its radiation pattern and the safe perimeter volume.

The invention is of interest for the inspection and testing of radar and radio-navigation system installations, terrestrial and satellite telecommunications systems, antennas on board aircrafts or ships, or terrestrial broadcasting installations.

COMPETITIVE ADVANTAGES

- ✓ Multiple applications: radar and radio-navigation system installations, terrestrial and satellite telecommunications systems, antennas on board aircrafts or ships, or terrestrial broadcasting facilities.
- ✓ Technical and implementation simplicity: a high investment for development is not required.
- ✓ Less operating costs: one operator, low supervision and low expertise needed. Less time for results.

Demo video:

<https://bit.ly/2GUBlam>

PATENTS

ES patent granted. International protection underway.

Certain protection expenses subsidised by the Government of Asturias, through FICYT, for the knowledge and tech transfer 2022. AYUD/2021/33531

TYPE OF COLLABORATION

Licence agreement.

Contact person

Yuri Álvarez López

Department

Electrical, Electronic, Computers and Systems Engineering

E.mail

otri@uniovi.es

Phone

(+34) 985 10 27 69
(+34) 985 18 23 29